



<b>Model</b>	SIT-CAM-R5610-3V-P
<b>Video format</b>	NTSC / PAL
<b>Number of pixels</b>	728 x 488
<b>Matrix</b>	1/3" Color CMOS
<b>Resolution (TV Lines)</b>	480 TV Line
<b>Lens</b>	Pinhole 3.7mm/F2.5(M9xP0.5 W/IR filter)
<b>Minimum lighting</b>	0.05 Lux
<b>Operating temperature</b>	from -10 to 50 degrees Celsius
<b>Feeding</b>	Camera input: DC 5~12V
<b>Consumption</b>	80mA(Max)
<b>Size (mm)</b>	10(D) x 34(L) mm



<b>Model</b>	SIT-CAM-R5910-3V-P P
<b>Video format</b>	EIA / CCIR
<b>Number of pixels</b>	728 x 488
<b>Matrix</b>	1/3" B/W CMOS Hybrid Sensitivity
<b>Resolution (TV Lines)</b>	550 TV Line
<b>Lens</b>	Pinhole 3.7mm/F2.5(M9xP0.5 W/IR filter)
<b>Minimum lighting</b>	0.05 Lux
<b>Operating temperature</b>	from -10 to 50 degrees Celsius
<b>Feeding</b>	Camera input: DC 5~12V
<b>Consumption</b>	80mA(Max)
<b>Size (mm)</b>	10(D) x 34(L) mm



<b>Model</b>	SIT-CAM-AHD-S41488-2V
<b>Video format</b>	AHD
<b>Number of pixels</b>	1280x720
<b>Matrix</b>	1/4" Color CCIQ Camera
<b>Resolution (TV Lines)</b>	720P
<b>Lens</b>	Pinhole M7
<b>Storage temperature</b>	from -30 to 50 degrees Celsius
<b>Operating temperature</b>	from -10 to 50 degrees Celsius
<b>Feeding</b>	Camera input: DC 5~12V
<b>Consumption</b>	80 mA(max)-DC 12V
<b>Size (mm)</b>	8.6 x 8.6 mm

