



<b>Model</b>	SIT-CAM-900 (900D)
<b>Video format</b>	NTSC / PAL
<b>Number of pixels</b>	NTSC 656 x 492 / PAL 786 x 576
<b>Matrix</b>	1/3" COMOS
<b>Resolution (TV Lines)</b>	520 TV Line
<b>Lens</b>	Pinhole M8
<b>Minimum lighting</b>	0.008 Lux
<b>Operating temperature</b>	from -10 to 50 degrees Celsius
<b>Feeding</b>	Camera input: DC 3.3~5V
<b>Consumption</b>	75 mA
<b>Size (mm)</b>	900: 9.5 x 9.5 x 12 mm   900D: 11 x 11 x 15 mm



### MINI VIDEO CAMERA "SIT-CAM-900 (900D)"



<b>Model</b>	SIT-CAM-S5610-2V
<b>Video format</b>	NTSC / PAL
<b>Number of pixels</b>	728 x 488
<b>Matrix</b>	1/3" CCIQ III Color Camera
<b>Resolution (TV Lines)</b>	480 TV Line
<b>Lens</b>	Pinhole M7
<b>Frames per second</b>	60 (NTSC) , 50 (PAL)
<b>Storage temperature</b>	from -30 to 60 degrees Celsius
<b>Minimum lighting</b>	0.05Lux
<b>Operating temperature</b>	from -10 to 45 degrees Celsius
<b>Feeding</b>	Camera input: DC 5~12V
<b>Consumption</b>	80 mA(max)-DC 12V
<b>Size (mm)</b>	10.5 x 10.5 mm

### MINI VIDEO CAMERA "SIT-CAM-S5610-2V"



<b>Model</b>	SIT-CAM-908
<b>Video format</b>	NTSC / PAL
<b>Number of pixels</b>	NTSC 656 x 492 / PAL 786 x 576
<b>Matrix</b>	1/3" COMOS
<b>Resolution (TV Lines)</b>	520 TV Line
<b>Lens</b>	Pinhole M12
<b>Minimum lighting</b>	0.008 Lux
<b>Operating temperature</b>	from -10 to 50 degrees Celsius
<b>Feeding</b>	Camera input: DC 3.3~6V
<b>Consumption</b>	75 mA
<b>Size (mm)</b>	D 15mm / H 27 mm

### MINI VIDEO CAMERA "SIT-CAM-908"

